

Intelligent UV/Vis Detector

UV-2070/2075



The JASCO Models UV-2070 and UV-2075 are the most compact, full featured UV/Visible detectors that have ever been offered. Occupying only 15 cm of bench space the UV-2070/2075 have versatile capabilities to cover the most complex needs of the modern analytical laboratory. To ensure the most sensitive and stable HPLC detection these detectors utilize a Czerny-Turner mount monochromator covering a wide wavelength range from 190 to 900 nm with deuterium and halogen lamps (Model UV-2070) and from 190 to 600 nm with deuterium lamp (Model UV-2075). The excellent optical characteristics and full programmability of the UV-2070/2075 combined in a compact package is truly a new benchmark in HPLC detection. The UV-2070/2075 can easily be interfaced with the JASCO HPLC system using the JASCO chromatography data systems. These packages offer full automation of all JASCO HPLC components including the UV-2075.

- **Compact UV/VIS Detector**

The small 15 cm wide and 15 cm high detector occupies minimal laboratory space and the lightweight 10 kg housing allows it to be easily moved from place to place.

- **Wide wavelength range**

The UV-2075 utilizes a Deuterium lamp to cover the range of 190 nm ~ 600 nm. For enhanced performance in the visible range the UV-2070 has both Deuterium and Halogen sources covering the range of 190 nm ~ 900 nm.

- **High sensitivity and extreme stability**

The advanced high throughput optical design results in low baseline noise level with minimal drift enabling accurate peak detection for even the highest sensitivity analyses. The tapered cell design eliminates baseline variation due to the change in the refractive index of the eluent.

- **Full intelligent functions**

Front panel programming allows up to 10 program files with up to 64 steps/file. Time programmable parameters include Wavelength, Range, Autozero, Response and Spectral scanning. Self-diagnostics functions are provided for start up hardware checks as well as monitoring for solvent leakage, lamp-off, etc. during operation. To extend lamp life, a timer is provided to shut off the lamp after completing the run.

- **A variety of flow cells**

Various cassette type flow cells are available including Micro, Preparative, Ultra High pressure for SFC and/or LC-MS, PTFE for biochemical samples, and Inert flow cell for biochemical samples or ion chromatography.

- **On-the-fly spectral scanning**

The fast scanning speed of the UV-2070/2075 allows measurement of the UV spectrum as fast as one second allowing on-the-fly spectral scanning. UV spectra can be obtained without stopping the pump or bypassing the flow. Up to 10 Spectra and a baseline can be stored in the on-board memory allowing scans to be acquired at every peak during a typical chromatographic run.



SPECIFICATIONS

Optical system

Monochromator:	Czerny-Turner mount
Spectral bandwidths:	8 nm
Wavelength accuracy:	±1 nm
Wavelength reproducibility:	±0.1 nm
Light source	
UV-2070:	Deuterium lamp 190 ~ 370 nm, Halogen lamp 371 ~ 900 nm
UV-2075:	Deuterium lamp 190 ~ 600 nm
Wavelength range	
UV-2070:	190 ~ 900 nm
UV-2075:	190 ~ 600 nm

Photometric system

Photometric method:	Dual beam photometry
Noise level:	±0.3 × 10 ⁻⁵ ABU (at 250 nm, with empty cell, response: STD)
Drift:	1×10 ⁻⁴ ABU/h (at 250 nm, with empty cell and in constant temperature)
Photometric range:	0.0005, 0.001, 0.0025, 0.005, 0.01, 0.02, 0.04, 0.08, 0.16, 0.32, 0.64, 1.28, 2.56 ABU/10mV, S (short)
Auto zero:	Provided (with base line function)
Response:	3 steps (FAST, STD and SLOW)

Flow through cell

Mounting:	Front loading cassette type with bulkhead union
Flow cell:	Tapered cell
Path length:	10 mm
Optional flow through cells:	Preparative flow cell, Micro flow cell, High pressure flow cell, PTFE flow cell, Inert flow cell, Capillary flow cell

Materials:

All materials in contact with solvent are fused silica, PTFE and stainless steel

Signal input/output

Output to recorder:	10 mV/full scale
Output to integrator:	1 V/AU, 0.2 V/0.2AU, 1 V/2AU
Others:	Marker output/input, Autozero input, LC-NET output/input, Program reset/run, Leak out

Self-diagnostics

For starting up:	ROM (memory), RAM (memory), DC power, C-MOS RAM (memory backed-up by battery), Grating driver/mechanism, Light source, Radiation intensity of the light source
During operation:	Lamp, Leak in cell, Grating driver
Programming:	64 steps, 10 files, up to 999.9 minutes in 0.1 min increments for Wavelength, Range, Auto Zero, Response, Time programming for spectral measurement

Spectral scanning:

UV-2070:	Possible in the range of 200 ~ 900 nm
UV-2075:	Possible in the range of 200 ~ 600 nm

Spectral memory:

11 memories available for spectra (1 for baseline), possible to process differential spectra with spectral memory function.

Auto lamp off:

Settable from 0.1 ~ 99.9 hours in 0.1 hour increments

Others

Dimensions:	150 (W) x 470 (D) x 150 (H) mm
Weight:	Approx. 10 kg
Power Input voltage:	AC100 ~ 240 V ±10% 50/60 Hz
Power consumption:	
UV-2070:	190 VA
UV-2075:	145 VA

STANDARD ACCESSORIES

Spare fuses	2 pcs
AC Power cable	1 pc

OPTIONAL ACCESSORIES

6824-H101A	Standard flow cell unit
6824-H102A	Preparative flow cell unit
6824-H103A	Micro flow cell unit
6824-H105A	High pressure flow cell unit (gasket: Au, window: sapphire)
6824-H106A	Straight cell unit, 8 µL, 10 mm path.
6824-H107A	Micro flow cell unit, tapered, 2.6 µL, 5 mm path
6824-H110A	Tapered flow cell unit, 17 µL, PEEK
6824-H118A	High pressure cell unit (for prep. LC)

ORDERING INFORMATION

6824-J002B	Model UV-2070	UV/VIS Detector (~ 900 nm)
6825-J002B	Model UV-2075	UV/VIS Detector (~ 600 nm)
6826-J002B	Model UV-2077	Multi-wavelength UV/VIS Detector
6832-J002B	Model MD-2015	Diode Array Detector (~ 900 nm)
6831-J002B	Model MD-2010	Diode Array Detector (~ 600 nm)
6829-J003B	Model FP-2020	Fluorescence Detector
6833-J002B	Model RI-2031	Refractive Index detector
6838-J002B	Model CD-2095	Circular Dichroism Detector
6837-J002B	Model OR-2090	Chiral Detector
6836-J002B	Model CL-2027	Chemiluminescence Detector
6818-J002B	Model PU-2080	HPLC Pump
6823-J003B	Model PU-2089	Quaternary HPLC Pump
6820-J002B	Model PU-2085	Semi-micro HPLC Pump
6821-J002B	Model PU-2086	Semi-preparative HPLC Pump
6822-J002B	Model PU-2087	Preparative HPLC Pump
6819-J002B	Model PU-2080i	Bio-inert HPLC Pump
6823-J004B	Model PU-2089i	Bio-inert Quaternary HPLC Pump
6828-J008B	Model AS-2059	Autosampler
6827-J005B	Model AS-2055	Autosampler
6827-J006B	Model AS-2057	Autosampler
6834-J002B	Model CO-2060	Column Oven
6835-J002B	Model CO-2065	Column Oven

● Specifications are subject to change without notice.



JASCO INTERNATIONAL CO., LTD.

4-21, Sennin-cho 2-chome, Hachioji, Tokyo 193-0835, Japan
 Tel: +81-42-666-1322 Fax: +81-42-665-6512 Internet: <http://www.jasoint.co.jp/english/index.html>
 Australia, China, Hong Kong, India, Indonesia, Iran, Korea, Malaysia, New Zealand,
 Pakistan, Philippines, Russia, Singapore, South Africa, Taiwan, Thailand

JASCO INCORPORATED

8649 Commerce Drive, Easton, Maryland 21601-9903, U.S.A
 Tel: +1-800-333-5272 Tel: +1-410-822-1220 Fax: +1-410-822-7526 Internet: <http://www.jascoinc.com>
 Canada, Costa Rica, Mexico, Puerto Rico, Argentina, Brazil, Chile, Colombia, Paraguay, Peru, Uruguay

JASCO EUROPE s.r.l.

Via Confalonieri 25, 23894 Cremella (Lc), Italy
 Tel: +39-039-956439 Fax: +39-039-958642 www.jasco-europe.com

JASCO Deutschland www.jasco.de, **JASCO UK** www.jasco.co.uk, **JASCO France** www.jascofrance.fr,
JASCO Benelux www.jasco.nl, **JASCO Spain** www.jasco-spain.com, **JASCO Scandinavia** www.jascoscandinavia.se

Austria, Finland, Greece, Hungary, Poland, Portugal, Romania, Switzerland, Algeria, Cyprus,
 Egypt, Israel, Jordan, Kuwait, Lebanon, Morocco, Saudi Arabia, Syria, Tunisia, Turkey, U.A.E.



Serving the global marketplace
 with Analytical Instrumentation

JASCO Corporation

2967-5, Inhikawa-cho, Hachioji, Tokyo 192-8537, Japan
<http://www.jasco.co.jp>

LLC05-0607 Printed in Japan