

Supercritical Fluid Extraction

SFE-4000 Series



JASCO

Performance
Innovation
Reliability

Supercritical Fluid Extraction (SFE) is a selective technique that extracts compounds from semi-solid to solid matrices and isolates the analyte(s) of interest by utilizing supercritical CO₂ as the primary constituent in the extraction fluid. The intrinsic low viscosity and high diffusivity of supercritical CO₂ produces extracts with superior purity and yield, while having lower operating costs compared to traditional hydrocarbon-based solvent extraction systems.


Table of Contents

System	
SFE Advantage	3
Analytical	4
Hybrid SFE	4
Semi-Prep SFE	5
Preparative SFE	5
Options	6
Specifications	7

SFE Advantage

Supercritical Fluid Extraction employs a supercritical fluid, most commonly CO₂, as the A mobile phase solvent for the extraction. The intrinsic low viscosity and high diffusivity of supercritical CO₂ has rendered SFE a faster extraction and higher efficiency technique when compared to traditional liquid extraction. This provides faster flow rates and thus faster extraction times without the requirement for a higher

pressure system. The addition of a co-solvent to the CO₂ flow can help tune the strength further. The extraction oven can offer temperatures up to 90°C. Lastly after the extraction vessel is the back pressure regulator, which provides the back pressure requirement to keep the CO₂ supercritical, and is an integral part of the performance of the extraction.



Advantages

1. **Selectivity** CO₂ polarity varies greatly depending upon the pressure it is exposed to. This makes CO₂ a tunable solvent which allows the user to find the precise conditions for extraction of the compounds of interest while leaving unwanted compounds behind. This inherent trait of CO₂ greatly reduces the need for post extraction cleanup that would be necessary with most solvent extractions.
2. **No Residual Solvents** Given the gaseous state of CO₂ at atmospheric conditions, the resulting extract does not require the long rotovap time needed to dry solvent extracted analytes.
3. **Faster** Given the high diffusivity and low viscosity of CO₂ in its supercritical state, the extractions typically take a fraction of the time compared to solvent extractions.
4. **Higher Yield** Due to increased temperature and pressure, supercritical CO₂ can penetrate many matrices that solvents cannot, thereby allowing for greater surface area contact which in turn increases yield.
5. **Low Operating Cost** Cost Per Extraction is significantly lower as the cost of CO₂ is much lower than the equivalent amount of solvent.
6. **Environmentally Friendly**

When compared to Soxhlet extractions, supercritical fluid extractions have proven to be capable of providing extractions up to 25 times faster with equivalent recovery while using up to 30 times less solvent.

Analytical & Hybrid SFE

Analytical SFE

The analytical CO₂ pump offers built-in Peltier cooling to maintain a stable CO₂ flow yielding excellent extraction time reproducibility. Automatic, built-in shut-off valves close the CO₂ inlet and outlet and isolate the pumps for quick and simple priming when not pumping.

The system can be configured for CO₂ only or 1-10 co-solvents, 1-10 extraction vessels for the vessel volumes listed above and 1, 6, 12 or 54 fractions.

System	Extraction Vessel	CO ₂ Flow Rate
Analytical	1mL, 5mL, 10mL	0.5 - 10mL

Hybrid SFE

The hybrid CO₂ pump offers a flow range from 0.5 to 20mL/min covering both analytical 10mL vessels up to semi-prep 100mL vessels. Automatic, built-in shut-off valves close the CO₂ inlet and outlet and isolate the pumps for quick and simple priming when not pumping.

The system can be configured for CO₂ only or 1-10 co-solvents, 1-10 extraction vessels for the vessel volumes listed above and 1, 6, 12 or 54 fractions.

System	Extraction Vessel	CO ₂ Flow Rate
Hybrid	10mL, 50mL, 100mL	0.5 - 20mL



Semi-Prep & Preparative SFE

Semi-Prep SFE

The semi-prep CO₂ pump offers a flow range from 5 to 40mL/min covering 50mL vessels up to 200mL vessels. Automatic, built-in shut-off valves close the CO₂ inlet and outlet and isolate the pumps for quick and simple priming when not pumping.



The system can be configured for CO₂ only or 1-10 co-solvents, 1-10 extraction vessels for the vessel volumes listed above and 1, 6, 12 or 54 fractions.

System	Extraction Vessel	CO ₂ Flow Rate
Semi-Preparative	50mL, 100mL, 200mL	0.5 - 40mL

Preparative SFE

The Prep CO₂ pump offers a flow range from 10 to 150mL/min covering 500mL vessels up to 2L vessels. Automatic, built-in shut-off valves close the CO₂ inlet and outlet and isolate the pumps for quick and simple priming when not pumping.

The system can be configured for CO₂ only or 1-10 co-solvents, 1-10 extraction vessels for the vessel volumes listed above and 1, 6, 12 or 54 fractions.

System	Extraction Vessel	CO ₂ Flow Rate
Preparative	500mL, 1L, 2L	10 - 150mL

Specifications

Supercritical Extraction System		
Pump Section	CO ₂ Flow Rates	0.5 - 7mL/min, 0.5 - 14mL/min, 5 - 40mL/min, 10 - 150mL/min
	CO ₂ Inlet Supply Pressure	55 - 90 bar
	CO ₂ Chiller	Operating at -10°C for optimal CO ₂ density
	Built-In Shut-Off Valves	Automatically controlled by pump and software
	Protection	Built-in shut off valves protect the CO ₂ pump
	Co-Solvent Flow Rates	0.5 - 7mL/min, 0.5 - 14mL/min, 5 - 40mL/min, 10 - 150mL/min
	Built-In Number of Co-Solvents Option	6 or 10 with automated software control
	Pump Pressure Range	60 - 500 bar
Oven Section	Extraction Oven Temperature	Ambient 15 - 90°C
	Heating Rate	Approximately 5°C/min
	Built-In Number of Extraction Vessels Options	10 extraction vessels
	Vessel Pressure	Up to 345 bar
	Vessel Options	1mL, 10mL, 50mL (other volume vessels are custom made)
Back Pressure and Fraction Section	Back Pressure Range	60 - 500 bar
	Pressure Control	± 2 bar or less for excellent extraction reproducibility
	Fraction Heater	For increased fraction recoveries
	Fraction Options	Waste and 1, 6, 12, or 54 fractions
System	Control	Front panel and complete software control
	Extraction Process Control	Process setup for complete automation in the software
	PC	Windows PC with flat panel monitor
	Power	110 - 220V, 50 to 60 Hz



JASCO INTERNATIONAL CO., LTD.

11-10, Myojin-cho 1-chome, Hachioji, Tokyo 192-0046, Japan
Tel: +81-42-649-3247 Fax: +81-42-649-3518 <http://www.jascoint.co.jp/english/>
Australia, Hong Kong, India, Indonesia, Korea, Malaysia, New Zealand,
Pakistan, Philippines, Russia, Singapore, Taiwan, Thailand, Vietnam

JASCO INCORPORATED

28600 Mary's Court, Easton, Maryland 21601, U.S.A.
Tel: +1-410-822-1220 Fax: +1-410-822-7526 Web: www.jascoinc.com
Argentina, Bolivia, Brazil, Canada, Chile, Colombia, Costa Rica, Guatemala, Mexico,
Paraguay, Peru, Puerto Rico, United States of America, Uruguay, Venezuela

JASCO EUROPE S.R.L.

Via Luigi Cadorna 1, 23894 Cremella (LC), Italy
Tel: +39-039-9215811 Fax: +39-039-9215835 Web: www.jascoeuropa.com
JASCO Deutschland www.jasco.de | **JASCO UK** www.jasco.co.uk | **JASCO France** www.jasco.fr
JASCO Benelux www.jasco.nl | **JASCO Spain** www.jasco-spain.com

Algeria, Austria, Belgium, Cyprus, Denmark, Egypt, Finland, France, Germany, Greece, Hungary, Iran, Iraq, Israel,
Italy, Jordan, Kuwait, Lebanon, Luxembourg, Morocco, Netherlands, Norway, Poland, Portugal, Romania, Saudi
Arabia, South Africa, Spain, Sweden Switzerland, Tunisia, Turkey, United Arab Emirates, United Kingdom, Yemen

JASCO China (Shanghai) Co., Ltd.

Room No.D, 10F, World Plaza, 855 Pudong South Road, Pudong New Area,chi
Tel: +86-21-6888-7871 Fax: +86-21-6888-7879 <http://www.jasco-global.com>



Products described herein are
designed and manufactured by
ISO-9001- and ISO-14001-certified
JASCO Corporation